




X100 Inhibitor

Protection against corrosion and limescale







Approximately 87% of boiler call-outs are to systems without correct water treatment.

Source: major boiler manufacturer testing and research

Scale and corrosion are often the primary causes of boiler and component failures.

In new high efficiency boilers it's crucial that the system is cleaned and protected.

Why use Sentinel X100 Inhibitor?

Corrosion and limescale lead to radiator cold spots, system breakdown and problems with components. Added after cleaning, Sentinel X100 Inhibitor provides continued protection for all types of indirect wet heating systems against corrosion and limescale, extending boiler life and maintaining an efficient, reliable system.

Save energy and money



Sentinel X100 Inhibitor is an Energy Saving Trust Endorsed Product

An increase of 1°C in room temperature increases the energy bill by 7%.

Source: Independent research conducted by Gastec@CRE

A recent British Gas Survey revealed that more than half of respondents (56%) had gone without heating for at least a day. 19% had even had to take one or more days off work because of boiler problems.

Source: British Gas customer research 2016

Use Sentinel X100 Inhibitor as part of The Sentinel System best practice approach to water treatment:



appropriate cleaner



Protect with Eliminator filter



Maintain with X100 Quick Test

Not sure which product you need? Try our product selector tool at: www.sentinelprotects.com/uk/product-selector

How Sentinel X100 Inhibitor works

Intelligent pH balancing

pH balancers keep system pH stable, preventing large swings in pH which can cause and accelerate corrosion of components such as heat exchangers.

Unique anti-corrosion formulation —

Superior blend of inhibitors to protect all system metals against corrosion, keeping the system water free of sludge.

Triple action limescale prevention

Prevents limescale deposits from forming which can damage pumps.

Suitable for hard, soft & softened water ——

COMPLETELY effective whatever the water supply to the property.





Easy to dose into a system

- 1. Ensure that system has been cleaned using the appropriate Sentinel cleaner and thoroughly flushed with fresh water.
- 2. X100 Inhibitor should then be dosed at 1% of system volume, i.e. 1 litre of Sentinel X100 to treat 100 litres of system water.

3. Open systems:

Dose via feed & expansion cistern, via a by-pass feeder or use a dosing vessel.

Sealed systems:

If the system is empty, add to any convenient point before filling. If full, use a dosing vessel to inject via the filling loop or other access point.

Rapid-Dose™

With Rapid-Dose, follow the instructions on the can to dose into a system in under a minute where the pressure is 2.3 bar or lower.



X100 Quick Test

Confirm correct level of inhibitor using the Sentinel X100 Quick Test Kit.

Trusted to protect





Endorsed by leading manufacturers



























Sentinel Performance Solutions Ltd

7650 Daresbury Park, Warrington, Cheshire, WA4 4BS, United Kingdom. Tel: +44 (0) 1928 704 330

www.sentinelprotects.com



